


姿図



品 番	LLG-7068NUW
光 源	LED 9.5W 4000K
定格光束	870.0 lm
1/2照度角	25 °
ビーム角	26 °

器具効率	100.0 %
上方光束	100.0 %
下方光束	0.0 %
器具間隔 最大限 (取付高さH)	A 0.44 H B 0.44 H
保 守 率	良 0.69 中 0.67 否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (×0.01)												
0.6		83	78	75	82	78	75	81	78	75	81	77	75	74
0.8		88	84	81	88	83	80	86	83	80	85	82	79	78
1		94	89	86	93	89	86	91	88	85	90	87	84	82
1.25		98	94	91	97	93	90	95	92	89	93	90	88	86
1.5		101	97	94	100	96	93	97	94	92	95	93	91	88
2		106	103	100	104	101	99	102	99	97	99	97	96	93
2.5		109	106	104	107	105	103	104	103	101	102	100	99	95
3		112	109	107	110	108	106	106	105	104	103	102	101	98
4		114	112	111	112	110	109	108	107	106	105	104	103	99
5		115	114	113	113	112	111	109	109	108	106	105	105	100

