






品 番	LKB-93058XW+LZA-92820WE
光 源	LED 16.4W 5000K
定格光束	2500 lm
照度角	64°
ビーム角	113°

器具効率	100.0 %
上方光束	3.4 %
下方光束	96.6 %
器具間隔 最大限 (取付高さH)	A 1.24H
保 守 率	良 0.83 中 0.81 否 0.77

天井 壁 床	80								70								50								30								20	0
	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	10	0
室指数	照 明 率																																(× 0.01)	
0.6	61	57	47	44	38	37	32	31	59	55	46	44	37	36	31	31	56	52	44	42	36	35	31	31	53	50	42	41	35	35	31	30	30	28
0.8	72	65	57	53	47	45	40	39	69	64	56	53	47	45	40	39	65	60	53	51	45	44	39	39	61	57	51	49	44	43	39	38	38	36
1	80	72	66	61	56	53	49	47	77	70	64	60	55	52	48	47	72	67	61	58	53	51	47	46	67	63	58	56	51	50	46	45	45	43
1.25	88	78	74	68	64	60	57	54	84	76	72	67	63	59	56	54	78	72	68	64	61	58	55	53	73	69	65	62	58	57	53	52	52	49
1.5	93	82	80	73	71	66	64	60	90	80	78	72	69	65	63	60	83	77	74	69	67	63	61	59	78	73	70	67	64	62	59	58	57	55
2	101	88	90	81	81	74	74	69	97	86	87	79	79	73	73	68	90	83	82	77	76	71	70	67	84	79	78	74	72	70	68	66	65	63
2.5	107	92	97	85	89	80	82	75	102	90	94	84	86	79	80	74	95	86	88	81	82	77	77	73	88	83	83	79	78	75	74	72	71	68
3	110	95	102	89	94	84	88	80	106	93	98	87	92	83	86	79	98	89	92	85	87	81	82	77	91	86	87	82	82	79	79	76	75	73
4	115	98	108	93	102	89	96	86	110	96	104	92	98	88	94	85	102	92	97	89	93	86	89	83	95	89	91	86	88	84	85	81	80	78
5	118	100	112	96	106	92	102	89	113	98	108	94	103	91	99	88	105	94	100	92	97	89	93	86	97	91	94	89	91	87	88	84	83	81
7	122	102	117	100	113	97	109	95	117	101	113	98	109	96	106	94	108	97	105	95	102	93	99	91	100	94	98	92	96	91	94	89	88	86
10	124	104	121	102	118	100	115	99	119	102	117	101	114	99	111	97	110	99	108	98	106	96	104	95	103	96	101	95	99	94	98	93	92	89



注)保守率は含みません。