





品 番	LZA-93794YSW
光 源	LDR4L-W-E11/D/S16V30
ランプ光束	460 lm
照度角	28°
ビーム角	31°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.51H
保 守 率	良 0.69 中 0.67 否 0.63

反 射 率 (%)	天井 壁 床	80								70								50								30								20	0		
		70		50		30		10		70		50		30		10		70		50		30		10		10	0										
		30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0								
室指数		照 明 率																																(× 0.01)			
0.6		89	82	79	76	73	71	70	68	88	81	79	75	73	71	69	68	85	80	77	75	72	71	69	68	83	79	76	74	72	71	69	68	68	67		
0.8		96	88	87	81	80	77	76	74	95	87	86	81	80	77	76	74	91	85	84	80	79	76	75	74	88	83	82	79	78	76	74	73	73	72		
1		102	92	93	87	87	83	82	80	100	91	92	86	86	82	82	79	96	89	90	85	85	82	81	79	93	88	87	84	83	81	80	79	78	77		
1.25		107	95	99	91	93	87	88	84	105	94	97	90	92	87	87	84	100	93	94	89	90	86	86	83	96	91	91	88	88	85	85	83	83	81		
1.5		111	98	103	94	97	90	93	88	108	97	101	93	96	90	92	87	103	95	98	92	93	89	90	87	99	93	95	90	91	88	88	86	86	84		
2		117	101	110	98	105	96	101	93	113	100	108	97	103	95	99	93	108	98	103	96	100	94	96	92	103	97	99	94	96	93	94	91	91	89		
2.5		120	104	114	101	110	99	106	97	117	103	112	100	108	98	104	97	110	101	107	99	104	97	101	96	105	99	102	97	100	96	98	95	94	93		
3		123	105	118	103	114	101	111	100	119	104	115	102	111	101	108	99	112	102	109	101	107	99	104	98	107	100	104	99	103	98	101	97	97	95		
4		125	106	121	105	118	104	116	103	121	105	118	104	115	103	113	102	114	103	112	102	110	102	108	101	108	102	107	101	105	100	104	99	99	97		
5		127	107	124	106	121	105	119	105	123	106	120	105	118	105	116	104	115	104	114	104	112	103	110	102	109	102	108	102	107	101	105	101	100	98		
7		129	109	127	108	126	108	124	107	125	108	123	107	122	107	121	107	117	106	116	105	115	105	114	105	111	104	110	104	109	103	108	103	102	101		
10		131	109	129	109	128	109	127	109	126	108	125	108	124	108	123	108	118	106	118	106	117	106	116	106	111	104	111	104	110	104	110	104	103	102		



注)保守率は含みません。