



品 番	DPN-40595YG
光 源	LDC4L-W-E17/D/C40V <DAIKO>
ランプ光束	385 lm
照度角	(A 36° A' 35°) B-B' 70°
ビーム角	(A 104° A' 119°) B-B' 219°

器具効率	70.9 %
上方光束	26.7 %
下方光束	44.2 %
器具間隔 最大限 (取付高さH)	A 1.47H B 1.41H
保 守 率	良 0.63 中 0.60 否 0.56

天井 壁 床 反射率 (%)	80								70								50								30								20	0		
	70		50		30		10		70		50		30		10		70		50		30		10		70		50		30		10		10	0		
	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	10	0				
室指数	照 明 率																														(×0.01)					
0.6	37	34	26	25	20	19	16	15	34	31	25	23	19	18	15	15	29	27	21	21	17	16	13	13	24	23	18	18	14	14	12	12	11	8		
0.8	44	40	33	31	26	25	21	21	40	37	31	29	24	24	20	20	34	32	27	25	21	21	18	17	29	27	23	22	19	18	16	15	14	11		
1	49	44	38	36	31	30	26	25	45	41	36	33	29	28	25	24	38	35	31	29	26	25	22	21	32	30	26	25	22	22	19	19	17	14		
1.25	54	48	44	40	37	34	31	30	50	45	41	38	34	32	29	28	42	39	35	33	30	29	26	25	35	33	30	29	26	25	23	22	21	17		
1.5	58	51	48	44	41	38	35	33	53	47	45	41	38	36	33	32	45	41	38	36	33	32	29	28	37	35	33	31	29	28	26	25	23	19		
2	63	55	55	49	48	44	42	39	58	51	51	46	45	41	40	37	49	45	43	40	39	37	35	33	41	38	37	35	33	32	30	29	27	23		
2.5	67	58	59	52	53	48	48	44	61	54	55	49	49	45	45	41	52	47	47	43	43	40	39	37	43	41	40	38	36	35	34	33	30	26		
3	69	60	62	55	57	50	52	47	64	56	58	51	53	48	48	44	54	49	49	45	45	42	42	40	45	42	42	40	39	37	36	35	33	28		
4	73	62	67	58	62	54	57	51	67	58	62	55	58	51	54	48	57	51	53	48	49	46	46	43	47	44	45	42	42	40	40	38	36	30		
5	75	64	70	60	65	57	61	54	69	60	65	57	61	54	57	51	58	53	55	50	52	48	49	46	49	46	47	44	44	42	42	40	38	32		
7	78	66	74	63	70	60	67	58	72	62	68	59	65	57	62	55	61	55	58	53	56	51	54	49	51	48	49	46	47	45	46	44	41	35		
10	80	67	77	65	74	63	72	61	74	63	71	62	69	60	67	58	62	56	61	55	59	53	57	52	53	49	51	48	50	47	49	46	43	37		

