


姿図



品 番

DDL-8795AW

光 源

LED5.8W 3500K

定格光束

360.0 lm

1/2照度角

26°

ビーム角

28°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.47 H B 0.47 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		62	55	51	61	55	51	60	55	50	59	54	50	49
0.8		71	64	59	70	64	59	69	63	59	67	62	58	56
1		79	72	67	78	71	67	76	70	66	74	69	65	63
1.25		85	79	74	84	78	74	82	77	73	80	75	72	69
1.5		90	84	80	89	83	79	86	82	78	84	80	77	74
2		97	92	88	96	91	87	93	89	86	90	87	84	81
2.5		102	97	94	100	96	93	97	93	91	94	91	89	85
3		105	101	98	103	100	97	99	97	94	96	94	92	88
4		108	105	103	106	104	101	102	100	98	99	97	96	91
5		110	108	106	108	106	104	104	102	101	101	99	98	93

