


姿図



品番	DWP-40274Y_天井付
光源	LDA5L-G/40W/B27K <DAIKO>
定格光束	500 lm
1/2照度角	80°
ビーム角	244°

器具効率	84.7 %
上方光束	28.7 %
下方光束	55.9 %
器具間隔 最大限 (取付高さH)	A 1.68 H
	B 1.68 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	
床	20			20			20			20			0		
室指数	照 明 率 ( × 0.01 )														
0.6	30	23	18	28	22	17	25	19	15	22	17	14	10		
0.8	38	30	24	35	28	23	31	25	21	27	22	18	14		
1	44	36	30	41	34	28	36	30	25	31	26	22	17		
1.25	50	42	35	47	39	34	41	35	30	35	31	27	20		
1.5	54	46	40	51	44	38	44	39	34	39	34	30	23		
2	61	54	48	57	51	46	50	45	41	44	39	36	28		
2.5	66	59	54	62	56	51	54	49	45	47	43	40	32		
3	70	63	58	65	60	55	57	53	49	50	46	43	34		
4	74	69	64	70	65	61	61	57	54	53	50	48	38		
5	77	73	69	73	68	65	64	60	57	55	53	51	40		

