

姿図



品番	LZW-60788AB
光源	LED 15W 3500K
定格光束	1310 lm
1/2照度角	60°
ビーム角	70°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.15 H
	B 1.15 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	75	70	66	75	70	66	74	69	66	73	69	66	64	
0.8	82	77	73	81	76	73	80	76	72	79	75	72	70	
1	88	83	79	87	83	79	86	81	78	84	80	78	76	
1.25	93	88	85	92	88	84	90	86	83	88	85	82	80	
1.5	97	93	89	96	92	88	93	90	87	91	88	86	83	
2	103	99	96	101	98	95	98	96	93	96	93	91	88	
2.5	106	103	100	105	102	99	101	99	97	99	97	95	92	
3	109	106	104	107	105	103	104	102	100	101	99	98	94	
4	112	109	108	110	108	106	106	104	103	102	101	100	96	
5	113	111	110	111	110	108	107	106	105	104	103	102	97	

