


姿図



品 番	DOL-5209YS
光 源	LED 4.8W 2700K Ra96
定格光束	220.0 lm
1/2照度角	33°
ビーム角	36°

器具効率	100.0	%	反射率 (%)	天井	80			70			50			30			0
上方光束	0.0	%		壁	50	30	10	50	30	10	50	30	10	50	30	10	0
下方光束	100.0	%		床	20			20			20			20			0
			室指数	照 明 率 (× 0.01)													
			0.6	82	78	75	82	78	75	81	77	74	80	77	74	73	
器具間隔	A	0.60 H	0.8	88	83	80	87	83	80	86	82	79	85	81	79	77	
最大限			1	93	89	86	92	88	85	91	87	85	89	86	84	82	
(取付高さH)	B	0.60 H	1.25	98	93	90	97	93	90	95	91	89	93	90	88	85	
			1.5	101	97	94	100	96	93	97	94	92	95	93	91	88	
	良	0.69	2	106	102	100	104	101	99	101	99	97	99	97	95	92	
			2.5	109	106	104	107	105	103	104	102	101	101	100	99	95	
	中	0.67	3	111	109	107	110	108	106	106	105	103	103	102	101	97	
			4	114	112	111	112	110	109	108	107	106	105	104	103	99	
保 守 率	否	0.63	5	115	114	113	113	112	111	109	108	108	106	105	104	100	

