


姿図



品番	DCL-40245A
光源	LED 12W 3500K
定格光束	970.0 lm
1/2照度角	A-A' 60° B-B' 61°
ビーム角	A-A' 88° B-B' 96°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さ H)	A 1.15 H
	B 1.18 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井				壁				床			
	80	70	50	30	80	70	50	30	80	70	50	30
室指数	照 明 率 (× 0.01)											
0.6	50	42	37	35	50	42	37	35	50	42	37	35
0.8	60	52	46	43	60	52	46	43	60	52	46	43
1	68	60	54	50	68	60	54	50	68	60	54	50
1.25	76	68	62	58	76	68	62	58	76	68	62	58
1.5	82	74	69	63	82	74	69	63	82	74	69	63
2	90	84	78	71	90	84	78	71	90	84	78	71
2.5	96	90	85	77	96	90	85	77	96	90	85	77
3	99	94	90	81	99	94	90	81	99	94	90	81
4	104	100	96	85	104	100	96	85	104	100	96	85
5	107	103	100	88	107	103	100	88	107	103	100	88

A - A'

B - B'

