


姿図



品 番	LZD-91948AW
光 源	LED 22W 3500K
定格光束	1560.0 lm
1/2照度角	28°
ビーム角	28°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.49 H B 0.49 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		79	74	71	79	74	71	78	73	71	77	73	70	69
0.8		85	80	77	84	80	76	83	79	76	82	78	75	74
1		91	86	83	90	86	82	88	84	81	87	83	81	79
1.25		96	91	88	94	90	87	92	89	86	90	87	85	83
1.5		99	95	91	98	94	91	95	92	89	93	90	88	86
2		104	101	98	103	100	97	100	97	95	97	95	93	90
2.5		108	105	102	106	103	101	103	101	99	100	98	97	93
3		110	108	106	109	106	104	105	103	102	102	101	100	96
4		113	111	109	111	109	108	107	106	105	104	103	102	98
5		114	113	112	112	111	110	108	107	107	105	104	103	99

