


姿図



品 番	LZD-91955YBV
光 源	LED 15W Q+3000K
定格光束	475 lm
1/2照度角	11°
ビーム角	11°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.19 H
保 守 率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		84	79	76	83	79	76	82	78	75	81	78	75	74
0.8		89	85	81	89	84	81	87	83	80	86	83	80	78
1		95	90	87	94	90	87	92	89	86	91	88	85	83
1.25		99	95	92	98	94	91	96	93	90	94	91	89	87
1.5		103	99	95	102	98	95	99	96	93	97	94	92	90
2		108	105	102	106	103	101	104	101	99	101	99	97	94
2.5		111	109	106	110	107	105	107	105	103	104	102	101	97
3		114	112	110	112	110	108	109	107	106	106	104	103	99
4		116	115	113	114	113	111	111	109	108	107	106	105	101
5		118	117	115	116	115	114	112	111	110	108	108	107	102

