


姿図



品 番	LZD-91948NB
光 源	LED 24W 4000K
定格光束	2300 lm
1/2照度角	27°
ビーム角	28°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.48 H B 0.48 H
保 守 率	良 0.69 中 0.67 否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		83	78	75	82	78	75	81	77	75	80	77	74	73
0.8		88	84	80	88	83	80	86	82	80	85	82	79	77
1		94	89	86	93	89	86	91	88	85	90	87	84	82
1.25		98	94	91	97	93	90	95	92	89	93	90	88	86
1.5		101	97	94	100	96	94	98	95	92	96	93	91	88
2		106	103	100	105	102	99	102	100	98	99	97	96	93
2.5		110	107	105	108	105	103	105	103	101	102	100	99	96
3		112	110	108	110	108	107	107	105	104	104	103	102	98
4		114	113	111	112	111	110	109	108	107	105	105	104	100
5		116	115	113	114	113	112	110	109	108	106	106	105	101

