


姿図



品 番	DPN-38288Y
光 源	LDA5L-G/40W/B27K x2 <DAIKO>
定格光束	1000 lm
1/2照度角	77°
ビーム角	284°

器具効率	88.8 %
上方光束	36.2 %
下方光束	52.6 %
器具間隔 最大限 (取付高さH)	A 1.59 H B 1.59 H
保 守 率	良 0.63 中 0.60 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		30	23	18	28	21	17	24	19	14	21	16	12	8
0.8		38	30	24	35	28	22	30	24	19	25	20	17	11
1		44	36	29	41	33	28	35	29	24	29	24	20	14
1.25		50	42	35	47	39	33	40	34	29	33	28	25	17
1.5		55	47	40	51	44	38	43	38	33	36	32	28	20
2		62	54	48	58	51	45	49	44	39	41	37	33	24
2.5		67	60	54	62	56	50	53	48	44	45	41	37	27
3		71	64	58	66	60	55	56	51	47	47	44	41	30
4		76	70	65	70	65	61	60	56	53	51	48	45	33
5		79	74	69	73	69	65	63	59	56	53	51	48	36

