


姿図



品 番	LZD-91956YB
光 源	LED 15W 3000K
定格光束	1130 lm
1/2照度角	20°
ビーム角	21°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.35 H B 0.35 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		83	79	76	83	79	76	82	78	75	81	78	75	74
0.8		89	84	81	88	84	81	87	83	80	86	82	80	78
1		94	90	87	93	89	86	92	88	86	90	87	85	83
1.25		99	94	91	98	94	91	96	92	90	94	91	89	86
1.5		102	98	95	101	97	94	98	95	93	96	94	92	89
2		107	103	101	105	102	100	102	100	98	100	98	96	93
2.5		110	107	105	108	106	104	105	103	102	102	101	100	96
3		112	110	108	111	109	107	107	106	104	104	103	102	98
4		115	113	112	113	111	110	109	108	107	106	105	104	100
5		116	115	114	114	113	112	110	109	109	107	106	105	101

