


姿図



品番	LZD-91953LB
光源	LED 10W 2700K
定格光束	690 lm
1/2照度角	22°
ビーム角	23°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.39 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20			20			20			20			0		
室指数	照 明 率 (× 0.01)														
0.6	79	74	71	79	74	71	78	74	71	77	73	71	69		
0.8	86	81	77	85	80	77	84	80	77	82	79	76	74		
1	92	87	83	91	86	83	89	85	82	88	84	82	80		
1.25	96	92	89	95	91	88	93	90	87	91	88	86	84		
1.5	100	96	92	99	95	92	96	93	91	94	91	89	87		
2	105	102	99	104	101	98	101	98	96	98	96	94	91		
2.5	109	106	103	107	104	102	104	102	100	101	99	98	94		
3	111	109	107	109	107	105	106	104	103	103	102	100	97		
4	114	112	110	112	110	109	108	107	106	105	104	103	98		
5	115	114	112	113	112	111	109	108	107	106	105	104	100		

