


姿図



品 番	DSL-5305FW
光 源	LED 8.8W 5000K-3500K-2700K
定格光束	400.0 lm
1/2照度角	61°
ビーム角	82°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.18 H B 1.18 H
保 守 率	良 0.69 中 0.67 否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		58	51	46	57	51	46	56	50	46	55	50	46	44
0.8		68	60	55	67	60	55	65	59	55	64	58	54	52
1		75	68	63	74	68	63	72	67	62	71	66	62	59
1.25		82	76	71	81	75	70	79	74	69	77	72	68	66
1.5		88	81	76	86	80	76	84	79	75	81	77	73	71
2		95	90	85	93	88	84	90	86	83	88	84	81	78
2.5		100	95	91	98	94	90	95	91	88	92	89	86	82
3		103	99	95	101	97	94	98	95	92	94	92	90	86
4		107	103	100	105	102	99	101	98	96	97	95	93	89
5		109	106	104	107	104	102	103	101	99	99	97	96	91

