


姿図



品番	LZD-92136YB
光源	LED 10W 3000K
定格光束	500 lm
1/2照度角	14°
ビーム角	14°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.24 H B 0.24 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20			20			20			20			0		
室指数	照 明 率 (× 0.01)														
0.6	83	79	75	83	78	75	82	78	75	81	77	75	73		
0.8	89	84	81	88	84	80	87	83	80	86	82	79	78		
1	94	90	86	93	89	86	92	88	85	90	87	85	83		
1.25	99	94	91	98	94	91	95	92	89	94	91	88	86		
1.5	102	98	95	101	97	94	98	95	93	96	94	91	89		
2	107	104	101	105	102	100	103	100	98	100	98	96	93		
2.5	110	107	105	109	106	104	105	103	102	103	101	100	96		
3	113	110	109	111	109	107	108	106	105	104	103	102	98		
4	115	113	112	113	112	110	109	108	107	106	105	104	100		
5	117	115	114	115	113	112	111	110	109	107	106	106	101		

