


姿図



品番	LZD-92803YWW
光源	LED 15W Q+3000K
定格光束	520 lm
1/2照度角	29°
ビーム角	31°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.51 H B 0.51 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	0
床	20			20			20			20			0		
室指数	照 明 率 ( × 0.01 )														
0.6	84	79	76	83	79	76	82	79	76	82	78	76	75		
0.8	89	85	81	89	84	81	87	84	81	86	83	80	79		
1	95	90	87	94	90	87	92	89	86	90	88	85	83		
1.25	99	95	91	98	94	91	96	92	90	94	91	89	87		
1.5	102	98	95	101	97	94	98	95	93	96	94	92	89		
2	107	103	101	105	102	100	102	100	98	100	98	96	93		
2.5	110	107	105	108	106	104	105	103	102	102	101	100	96		
3	112	110	108	111	109	107	107	106	104	104	103	102	98		
4	115	113	112	113	111	110	109	108	107	106	105	104	100		
5	116	115	114	114	113	112	110	109	109	106	106	105	101		

