


姿図



品 番	LZD-92285AWV
光 源	LED 25W Q+3500K
定格光束	1690.0 lm
1/2照度角	41 °
ビーム角	46 °

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.75 H B 0.75 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (×0.01)												
0.6		82	77	74	81	77	74	80	77	74	80	76	74	72
0.8		88	83	80	87	82	79	86	82	79	84	81	78	77
1		93	89	85	92	88	85	91	87	84	89	86	83	82
1.25		97	93	90	96	92	89	94	91	88	92	90	87	85
1.5		101	97	94	99	96	93	97	94	92	95	92	90	88
2		106	102	100	104	101	99	101	99	97	99	97	95	92
2.5		109	106	104	107	105	103	104	102	101	101	100	98	95
3		111	109	107	110	108	106	106	105	103	103	102	101	97
4		114	112	110	112	110	109	108	107	106	105	104	103	99
5		115	114	113	113	112	111	109	108	108	106	105	104	100

