


姿図



品番	DWP-37132E_天井付
光源	LDA5L-G/40W/B27K <DAIKO>
定格光束	500 lm
1/2照度角	71°
ビーム角	168°

器具効率	84.2 %
上方光束	23.8 %
下方光束	60.4 %
器具間隔 最大限 (取付高さH)	A 1.42 H
	B 1.42 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
室指数	照 明 率 (× 0.01)														
0.6	31	24	19	30	23	19	27	21	17	24	19	16	12		
0.8	39	31	26	37	30	24	33	27	22	29	24	21	16		
1	45	37	31	43	35	30	38	32	27	34	29	25	20		
1.25	51	43	37	48	41	35	43	37	32	38	33	29	24		
1.5	55	48	42	52	46	40	47	41	36	42	37	33	27		
2	62	55	49	59	53	47	53	47	43	47	43	39	32		
2.5	67	61	55	63	58	53	57	52	48	50	46	43	36		
3	71	65	59	67	61	57	60	55	51	53	49	46	38		
4	75	70	66	71	67	62	63	60	56	56	53	51	42		
5	78	74	70	74	70	66	66	63	60	59	56	54	45		

