


姿図



品 番	DDL-4790YB
光 源	LED 8.5W 2700K
定格光束	490.0 lm
1/2照度角	60 °
ビーム角	84 °

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.15 H B 1.15 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		59	52	47	58	52	47	57	51	47	56	51	47	45
0.8		69	62	57	68	62	57	67	61	56	65	60	56	54
1		77	70	65	76	70	65	74	69	64	72	68	64	61
1.25		84	78	73	83	77	73	81	76	72	79	74	71	68
1.5		89	83	79	88	83	78	86	81	77	83	79	76	73
2		97	92	87	95	91	87	92	88	85	89	86	83	80
2.5		101	97	93	100	95	92	96	93	90	93	90	88	85
3		104	101	97	103	99	96	99	96	94	96	94	91	88
4		108	105	102	106	103	100	102	100	98	98	97	95	91
5		110	107	105	108	105	103	104	102	100	100	98	97	92

